

Antenna coupling apparatus for cordless telephone

Publication number: JP6508019 (T)

Publication date: 1994-09-08

Inventor(s):

Applicant(s):

Classification:

- international: H01Q1/08; H01Q1/24; H01Q7/00; H04B1/034; H04B1/08; H04B1/38; H04Q7/14; H04Q7/32; H01Q1/08; H01Q1/24; H01Q7/00; H04B1/02; H04B1/08; H04B1/38; H04Q7/14; H04Q7/32; (IPC1-7): H01Q1/24; H01Q7/00; H04B1/034; H04B1/08; H04B1/38; H04B7/26

- European: H01Q1/08C; H01Q1/24; H01Q1/24A1; H01Q1/24A1A

Application number: JP19930519233T 19930128

Priority number(s): WO1993US00789 19930128; US19920873850 19920427

Also published as:


US5170173 (A)
WO9322803 (A1)
MX9302411 (A)
IT1262357 (B)
GB2271887 (A)

more >>

Abstract not available for JP 6508019 (T)

Abstract of corresponding document: US 5170173 (A)

The antenna coupling apparatus of the present invention couples an antenna, located in a hinged element (102) of a wireless communication device, to the receiver (401) of the device. In the preferred embodiment, the communication device is a radiotelephone. The coupling is achieved without contact or flexible cable by parallel plate capacitors (201 and 202) in the hinge of the communication device. The capacitors (201 and 202) additionally act as a matching network for the antenna.



Data supplied from the **espacenet** database — Worldwide